

# DranTech XTRA/PRO

TRMS Digital Multimeters



- Digital Hand-Held Multimeter with RMS Measurement: VAC TRMS, VAC+DC TRMS, VDC, Hz (V), Hz (A),  $\Omega$ , V, °C/°F (TC)
- 4  $\frac{3}{4}$  -digit display (60.000 counts), with backlight display
- Direct Current measurement with increased accuracy and Current measurement, via current clamp transformer and sensors
- Data Storage of Min-Max Values
- Automatic or Manual Measuring Range Selection
- Analog Scale for Quick Trend Indication – Bar Graph or Pointer
- Rugged with Protective Rubber Holster



XTRA only : remote configured, and momentary and stored measurement data via the bidirectional infrared Interface with DranWin software

## Applications

These digital multimeters are suitable for universal use in electrical engineering, electrical installation, laboratory applications, telecommunication, technical training, as well as for troubleshooting in the field.

## Features

### Three Connector Terminals with patented Automatic Blocking Sockets \*

All current ranges are implemented via a single connector socket which prevents any possibility of operator error. Beyond this, the automatic blocking sockets prevent incorrect connection of the measurement cables, as well as selection of the wrong measured quantity. Danger to the user, the instrument and the device under test resulting from operator error is therefore eliminated.

\* Patented (patent no. DE 40 27 801 C2 and US 5,166,599)

### Overload Protection

The instrument is safeguarded for up to 1000 V in all measuring functions by overload protection. Voltages of greater than 1000 V and current of greater than 10 or 16 A are indicated acoustically.

### RMS Value with Distorted Waveforms

The measuring method applied allows for waveform independent RMS measurement (TRMS AC and AC+DC) for voltage and current up to 10 kHz).

### Selectable Filter for V AC Measurement

A 1 kHz low-pass filter can be activated if required, for example when measuring motor voltage at electronic frequency converters.

### Battery Capacity Indication – Power Saving Circuit

The battery load capacity is indicated on the display. If user selected, the device is switched off automatically if the measured value remains unchanged for a period of between 10 and 59 minutes (adjustable), and if none of the controls are activated during this time.

### DKD Calibration Certificate

Multimeters are furnished with an internationally accepted DKD calibration certificate (recognized by EA and ILAC). After the specified calibration interval has elapsed (recommended interval: 1 to 3 years), the multimeters can be inexpensively recalibrated by any calibration laboratory.

### Scope of Delivery

- Multimeter with 1 pair of safety test leads (1.5 m) with 4 mm diameter, 1000 V CAT III, 600 V CAT IV (KS17-2)
- 2 alkaline batteries, 1.5 V, type AA
- CD with operating instructions,
- DKD calibration certificate
- Pack of 10 superfast Fuses 10A/1kV
- HC20 Hardcase

## Applicable Regulations and Standards

IEC 61010, Part 1:2001	Safety requirements for electrical equipment for measurement, control and laboratory use
IEC 61326	Electrical equipment for control technology and laboratory use – EMC requirements
IEC 60529	Test instruments and test procedures – degrees of protection provided by enclosures (IP code)

## Warranty

24 months for materials and workmanship  
1 to 3 years for calibration (depending upon application)

## Internal Clock

Time format DD.MM.YYYY hh:mm:ss  
Resolution 0.1 s  
Accuracy  $\pm 1$  min. per month  
Temperature Influence 50 ppm/K

## Power Supply

Battery 2 ea. 1.5 V, size AA, alkaline manganese per IEC LR6 (2 ea. 1.2 V NiMH rechargeable battery possible)  
Service life with alkaline manganese: approx. 200 hours  
Battery test: Battery capacity display with battery symbol in 4 segments: .  
Display of momentary battery voltage via menu function.  
Power OFF function: Multimeter is switched off automatically:  
– If battery voltage drops to below approx. 1.8 V  
– If none of the keys or the rotary switch are activated for an adjustable duration of 10 to 59 minutes, and the multimeter is not in continuous operating mode

## Fuse

Fuse FF (UR) 10 A/1000 V AC/DC; 10 mm x 38 mm, Switching capacity: 30 kA at 1000 V AC/ DC, protects the current measurement input in the 100  $\mu$ A through 10 A ranges

## Display

**LCD panel** (65 mm x 36 mm) with analog and digital display including unit of measure, type of current and various special functions

**Background illumination** is switched off approximately 1 minute after it has been activated (backlit display)

## Analog

Display LCD scale with bar graph or pointer, depending on the selected parameter setting  
Scaling With 4 division lines each, 1 bar/pointer corresponds to 500 digits at the digital display  
Polarity display In auto-ranging mode  
Overflow display With the symbol   
Update rate 40 measurements per second and display refresh

## Digital

Display/char 7-segment characters / 15 mm height  
Resolution 4  $\frac{3}{4}$  digits, 60,000 counts  
Overflow display "OL" is displayed for  $\geq 60,000$   
Polarity display "-" (minus sign) is displayed if pos. lead is connected to "⊥"  
Measuring rate 10 and 40 measurements per second with the Min-Max function except for the capacitance, frequency and duty cycle measuring functions  
Refresh rate 2 times per sec., every 500 ms

## Acoustic Signals

For voltage: Intermittent signal at above 1000 V  
For current: Intermittent signal at above 10 A  
Continuous signal at above 16 A

## Electrical Safety

Per IEC 61010-1:2001  
Cat. III 1000 V - Cat. IV 600 V  
Test voltage 6.7 kV~

## Electromagnetic Compatibility EMC

Interference emission	IEC 61326: May 2004, class B
Interference immunity	IEC 61326: May 2004, appendix E IEC 61000-4-2: Dec. 2001
Feature B	8 kV atmospheric discharge 4 kV contact discharge
Feature A	IEC 61000-4-3: Dec. 2001 3 V/m

## Ambient Conditions (to meet all specs)

Accuracy range	0 °C ... +40 °C
Operating temp. range	-10° C ... +50° C
Storage temp. range	-25° C ... +70° C (w/o batteries)
Relative humidity	Max.95%, no condensation allowed
Elevation	To 2000 m
Deployment	Indoors, except within specified ambient conditions

## Mechanical Design

Housing	Impact resistant plastic (ABS)
Dimensions	200 x 87 x 45 mm (without protective rubber holster)
Weight	Approx. 0.35 kg with batteries
Protection Housing:	IP 52

## Specifications

Meas. Function	Measuring Range	Resolution at Upper Range Limit		Input Impedance		Intrinsic Error under Reference Conditions			Overload Capacity <sup>2)</sup>	
		11,999	1199	∞	~ / ∞	±(... % rdg. + ... d)	±(... % rdg. + ... d)	±(... % rdg. + ... d)	Value	Time
V	100 mV	10 µV		≥ 9 MΩ	≥ 9 MΩ // < 50 pF	0.09 + 5 with ZERO	1 + 30 (> 300 d) <sup>1)</sup>	1 + 30 (> 300 d) <sup>1)</sup>	1000 V DC AC RMS sine <sup>6)</sup>	Continuous
	1 V	100 µV		≥ 9 MΩ	≥ 9 MΩ // < 50 pF	0.05 + 3	0.5 + 9 (> 200 d)	1 + 30 (> 300 d)		
	10 V	1 mV		≥ 9 MΩ	≥ 9 MΩ // < 50 pF	0.05 + 3	0.5 + 9 (> 200 d)	1 + 30 (> 300 d)		
	100 V	10 mV		≥ 9 MΩ	≥ 9 MΩ // < 50 pF	0.05 + 3	0.5 + 9 (> 200 d)	1 + 30 (> 300 d)		
	1000 V	100 mV		≥ 9 MΩ	≥ 9 MΩ // < 50 pF	0.09 + 3	0.5 + 9 (> 200 d)	1 + 30 (> 300 d)		
				Voltage drop, approx. at upper range limit		∞	~ 10)	∞ 10)		
A X-TRA Pro	100 µA	10 nA		12 mV	12 mV	0.5 + 5	1.5 + 10 (> 200 d)	1.5 + 30 (> 200 d)	0,2 A	dauernd
	1 mA	100 nA		120 mV	120 mV	0.5 + 3	1.5 + 10 (> 200 d)	1.5 + 30 (> 200 d)		
	10 mA	1 µA		16 mV	16 mV	0.5 + 3	1.5 + 10 (> 200 d)	1.5 + 30 (> 200 d)		
	100 mA	10 µA		160 mV	160 mV	0.5 + 3	1.5 + 10 (> 200 d)	1.5 + 30 (> 200 d)		
	1 A	100 µA		40 mV	40 mV	0.9 + 10	1.5 + 10 (> 200 d)	1.5 + 30 (> 200 d)	10 A: 5 min	
	10 A	1 mA		600 mV	600 mV	0.9 + 10	1.5 + 10 (> 200 d)	1.5 + 30 (> 200 d)	16 A: 30 s	
				Open-circuit voltage Meas. curr. @ range limit		±(... % rdg. + ... d)				
Ω	100 Ω	10 mΩ		< 1.4 V	Approx. 300 µA	0.2 + 5 with active ZERO function			1000 V DC AC RMS sine	Max. 10 s
	1 kΩ	100 mΩ		< 1.4 V	Approx. 250 µA	0.2 + 5				
	10 kΩ	1 Ω		< 1.4 V	Approx. 100 µA	0.2 + 5				
	100 kΩ	10 Ω		< 1.4 V	Approx. 12 µA	0.2 + 5				
	1 MΩ	100 Ω		< 1.4 V	Approx. 1.2 µA	0.2 + 5				
	10 MΩ	1 kΩ		< 1.4 V	Approx. 125 nA	0.5 + 10				
	40 MΩ	10 kΩ		< 1.4 V	Approx. 20 nA	2.0 + 10				
∅)	100 Ω	—	0.1 Ω	Approx. 8 V	Approx. 1 mA const.	1 + 5				
→)	5,1 V <sup>3)</sup>	—	1 mV	Approx. 8 V	Approx. 1 mA const.	0.5 + 3				
				Discharge resist. U <sub>0 max</sub>		±(... % rdg. + ... d)				
F X-TRA	10 nF	10 pF		10 MΩ	0.7 V	1 + 6 <sup>4)</sup> with ZERO function active			1000 V DC AC RMS sine	Max. 10 s
	100 nF	100 pF		1 MΩ	0.7 V	1 + 6 <sup>4)</sup>				
	1 µF	1 nF		100 kΩ	0.7 V	1 + 6 <sup>4)</sup>				
	10 µF	10 nF		12 kΩ	0.7 V	1 + 6 <sup>4)</sup>				
	100 µF	100 nF		3 kΩ	0.7 V	5 + 6 <sup>4)</sup>				
	1000 µF	1 µF		3 kΩ	0.7 V	5 + 6 <sup>4)</sup>				
				f <sub>min</sub> <sup>5)</sup>		±(... % rdg. + ... d)				
Hz (V)	100.00 Hz	0.01 Hz			1 Hz	0.05 + 3 <sup>8)</sup>			Hz (V) <sup>6)</sup> Hz (A <sup>7)</sup> <sup>6)</sup> 1000 V Hz (A) <sup>7)</sup>	Max. 10 s
Hz (A)	1.0000 KHz	0.1 Hz								
Hz (A <sup>7)</sup> )	10.000 KHz	1 Hz								
Hz (V)	100.00 KHz	10 Hz								
Hz (A)	30.00 KHz	10 Hz								
MHz X-TRA	100 Hz ... 1 MHz	100 Hz		100 Hz		0.05 + 3	> 2 V ... 5 V			

## Specifications (cont'd)

% X-TRA	2.0 ... 98 %	—	0.01%	100 Hz ... 1 kHz	1 Hz	0.1 R	> 2 V ... 5 V	1000 V	Max. 10 s
	5.0 ... 95 %	—	0.01%	... 10 kHz	1 Hz	0.1 R per kHz	> 2 V ... 5 V		
	10 ... 90 %	—	0.01%	... 100 kHz	1 Hz	0.1 R per kHz	> 2 V ... 5 V		
							±(... % rdg. + ... d)		
°C/°F	Pt100 X-TRA	-200.0 ... +850.0° C	0.1 °C				0.3 + 15 <sup>9)</sup>	1000 V DC/AC RMS Sine	Max. 10 s
	Pt1000 X-TRA	-150.0 ... +850.0° C					0.3 + 15 <sup>9)</sup>		
	K (NiCr-Ni)	-250.0 ... +1372.0° C					1% + 5 K <sup>9)</sup>		

- 1) Values of less than 200 digits are suppressed in the mV range.  
15 (20) ... 45 ... 65 Hz ... 20 (1) kHz sinusoidal. See influence error on page 4.  
2) At 0° ... + 40° C  
3) Displays up to max. 5.1 V, "OL" in excess of 5.1 V.  
4) Applies to measurements at film capacitors  
5) Lowest measurable frequency for sinusoidal measuring signals symmetrical to the zero point  
6) Overload capacity of the voltage measurement input:  
power limiting: frequency x voltage max.  $3 \times 10^6$  V x Hz for U > 100 V

- 7) Overload capacity of the current measurement input:  
See current measuring ranges for maximum current values.  
8) Input sensitivity, sinusoidal signal, 10% to 100% of the measuring range  
9) Plus sensor deviation  
10) Residual value deviates within 1 ... 30 d from the zero point due to TRMS converter when probe tips are short-circuited

Key: R = measuring range, d= digit(s), rdg. = measured value (reading)

## Data Interface

Type	Optical via infrared light through the housing
Data transmission	Serial, bidirectional (not IrDa compatible)
Protocol	Device specific
Baud rate	38,400 baud
Functions	<ul style="list-style-type: none"> <li>– Select/query measuring functions and parameters</li> <li>– Query momentary measurement data</li> <li>--Read out stored measurement data</li> </ul>

The USB plug-in interface adapter (see accessories) is used for adaptation to the PC's USB port.

## Internal Measured Value Storage (XTRA only)

Memory capacity 4 MBit / 540 kB for approx. 15,400 measured values with date and time stamp



www.dranetz-bmi.com

1.800.372.6832 [sales@dranetz-bmi.com](mailto:sales@dranetz-bmi.com)  
tel 732.287.3680 : fax 732.248.1834  
1000 New Durham Road,  
Edison, New Jersey 08818 USA

© 2008 Dranetz-BMI. All rights reserved.  
Printed in United States. Specifications are  
subject to change without notice.



CAT IV



DKD Calibration  
Certificate

DranTech PRO/XTRA Rev 1-March-08